

PF/KS 97.5 Licenses

United States of America

RECEIVED

FEDERAL COMMUNICATIONS COMMISSION

MAR 2 1992

FM BROADCAST STATION LICENSE

MINNESOTA PUBLIC RADIO



Official Mailing Address:

Authorizing Official:

for Dale E. Brokel

MINNESOTA PUBLIC RADIO
45 EAST 7TH STREET
ST. PAUL, MN 55101

Dennis L. Williams
Chief, FM Branch
Audio Services Division
Mass Media Bureau

Grant Date: 27 FEB 1992

Call sign: KSJN

This license expires 3:00 am.
local time: April 01, 1997

License File No.: BLH-910814KH

This license covers Permit No.: BPH-850711IG
as extended by Permit No.: BMPH-900813JF

and replaced by Permit No.: BPH-910507JK

Subject to the provisions of the Communications Act of 1934, subsequent acts and treaties, and all regulations heretofore or hereafter made by this Commission, and further subject to the conditions set forth in this license, the licensee is hereby authorized to use and operate the radio transmitting apparatus herein described.

This license is issued on the licensee's representation that the statements contained in licensee's application are true and that the undertakings therein contained so far as they are consistent herewith, will be carried out in good faith. The licensee shall, during the term of this license, render such broadcasting service as will serve the public interest, convenience, or necessity to the full extent of the privileges herein conferred.

This license shall not vest in the licensee any right to operate the station nor any right in the use of the frequency designated in the license beyond the term hereof, nor in any other manner than authorized herein. Neither the license nor the right granted hereunder shall be assigned or otherwise transferred in violation of the Communications Act of 1934. This license is subject to the right of use or control by the Government of the United States conferred by Section 606 of the Communications Act of 1934.

Name of Licensee:

MINNESOTA PUBLIC BROADCASTING

Station Location:

MN-MINNEAPOLIS

Frequency (MHz): 99.5

Channel: 258

Class: C

Hours of Operation: Unlimited

Main Studio Address:

MN-45 EAST 7TH STREET, ST. PAUL, RAMSEY COUNTY

Transmitter location (address or description):

550 GRAMSIE ROAD, SHOREVIEW, RAMSEY COUNTY, MINNESOTA

Remote control point address:

MN-45 EAST 7TH STREET, ST. PAUL, RAMSEY COUNTY

Transmitter: Type accepted. See Sections 73.1660, 73.1665 and 73.1670 of the Commission's Rules.

Transmitter output power (kW): 18.5

Antenna type: (directional or non-directional): Non-directional

Desc: ALAN DICK & CO. TYPE F88-108C12.3SP26OND2, 12 SECTIONS CIRCULARLY POLARIZED, SIDE-MOUNTED ON A GUYED STEEL TOWER

Antenna coordinates: North Latitude: 45 03 30.0 West Longitude: 93 07 27.0

	Horizontally Polarized Antenna	Vertically Polarized Antenna
Effective radiated power in the horizontal plane (kW) :	100.0	100.0
Height of radiation center above ground (meters) :	316.0	316.0

Height of radiation center above
mean sea level (meters) : 593.0 593.0

Height of radiation center above
average terrain (meters) : 315.0 315.0

Overall height of antenna structure above ground (including obstruction
lighting, if any) : 447.0 meters

Obstruction marking and lighting specifications for antenna
structure:

It is to be expressly understood that the issuance of these specifications
is in no way to be considered as precluding additional or modified marking
or lighting as may hereafter be required under the provisions of Section
303(g) of the Communications Act of 1934, as amended.

Paragraph 1.0, FCC Form 715 (March 1978):

Antenna structures shall be painted throughout their height with
alternate bands of aviation surface orange and white, terminating with
aviation surface orange bands at both top and bottom. The width of the
bands shall be equal and approximately one-seventh the height of the
structure, provided however, that the bands shall not be more than 100
feet nor less than 1 and 1/2 feet in width. All towers shall be
cleaned and repainted as often as necessary to maintain good
visibility.

Paragraph 3.0, FCC Form 715 (March 1978):

There shall be installed at the top of the structure one 300 m/m
electric code beacon equipped with two 620- or 700-watt lamps (PS-40,
Code Beacon type), both lamps to burn simultaneously, and equipped
with aviation red color filters. Where a rod or other construction of
not more than 20 feet in height and incapable of supporting this
beacon is mounted on top of the structure and it is determined that
this additional construction does not permit unobstructed visibility
of the code beacon from aircraft at any normal angle of approach,
there shall be installed two such beacons positioned so as to insure
unobstructed visibility of at least one of the beacons from aircraft
at any normal angle of approach. The beacons shall be equipped with a
flashing mechanism producing not more than 40 flashes per minute nor
less than 12 flashes per minute with a period of darkness equal to
approximately one-half of the luminous period.

Paragraph 10.0, FCC Form 715 (March 1978):

On levels at approximately four-fifths, three-fifths, two-fifths and one-fifth of the over-all height of the tower one similar flashing 300 m/m electric code beacon shall be installed in such position within the tower proper that the structural members will not impair the visibility of this beacon from aircraft at any normal angle of approach. In the event these beacons cannot be installed in a manner to insure unobstructed visibility of the beacons from aircraft at any normal angle of approach, there shall be installed two such beacons at each level. Each beacon shall be mounted on the outside of diagonally opposite corners or opposite sides of the tower at the prescribed height.

Paragraph 19.0, FCC Form 715 (March 1978):

On levels at approximately nine-tenths, seven-tenths, one-half, three-tenths and one-tenth of the over-all height of the tower, at least one 116- or 125-watt lamp (A21/TS) enclosed in an aviation red obstruction light globe shall be installed on each outside corner of the structure.

Paragraph 21.0, FCC Form 715 (March 1978):

All lighting shall burn continuously or shall be controlled by a light sensitive device adjusted so that the lights will be turned on at a north sky light intensity level of about 35 foot candles and turned off at a north sky light intensity level of about 58 foot candles.